Pro XD Full-Size Kinetic



Key Specifications

Electric

1,500

Fuel Type

Ibs Payload

1,000 Miles

Maintenance Interval

ANSI/OPEI Certification

Polaris Industries Inc. certifies that these vehicles complies with the American National Standard for Multipurpose off-Highway Utility Vehicles, ANSI/OPEI B71.9 – 2016 Standard

Engine & Drivetrain

Battery Range	45 miles
Cooling	Active Air & Liquid
Drive System Type	On-Demand 4x4 or High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Type	Internal Permanent Magnet AC Motor
Horsepower/Torque	110 HP / 140 ft lbs
Maintenance Interval	1,000 Miles (500 Miles initial break-in)
Top Speed	Adjustable up to 40 mph (64 km/h)
Top Towing Speed	10 mph (normal terrain) 5 mph (rough terrain)
Transmission/Final Drive	Gates Synchronous Belt H/L/N/P (Electronic Forward/Reverse), Shaft

Dimensions

Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in (93.3 x 137.8 x 31.75 cm)
Box Capacity	1,250 lb (567 kg)
Estimated Dry Weight	1,745 lb (792 kg)
Ground Clearance	12 in (30.48 cm)
GVWR	3,600 lb (1,632 kg)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising.

Manage Settings

Accept

Decline All

Turning Radius	13.3 ft (406.4 cm)	
Wheelbase	81 in (205.7 cm)	

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park in Transmission + Separate Mechanical Parking Brake Standard

Additional Specifications

Adjustable Driver Seat	Not Equipped
Cargo System	Lock & Ride
Charging Kit Included (EVSE)	J1772, Combined Level 1 / Level 2 Mobile
Engine Brake System (EBS)	Regenerative braking
Hitch Type	Standard 2 in (5 cm) Receiver
Instrumentation	Driver's Side Dual-sweep Analog Dials w/ 4" Multi-Color LCD Rider Information Center: Power Use and Regen %, Battery State of Charge %, Range Remaining, Charging Rate, Battery Temperature, Motor Temperature, Accessory Voltage, Speedometer, Odometer, Tripmeter, Gear Indicator, Service Indicator and Codes, Programmable Service Intervals, Seat Belt Reminder, User Selectable Backlighting & Brightness, Clock, Parking Brake Engaged Alarm
Lighting	Dual LED Headlamps, 1250lm low beam, 2300lm high beam, Dual LED Taillamps
Onboard Battery Charger	3kW Charger
Other Standard Features	Horn, backup alarm, password protected, electronically adjustable speed limiting, Polaris Pulse Electrical System, *Connected vehicle capability with the Polaris app, via RIDE COMMAND+
Seat Covering	Kevlar®-Backed Vinyl (Grey)
Tilt Steering	Standard

Tires / Wheels

Electronic Power Steering	Standard
Front Tires	Wanda OBOR TERRAREX 27x10-14
Hubs	Front: Ductile Iron; Rear: Ductile Iron
Rear Tires	Wanda OBOR TERRAREX 27x10-14
Wheels	14 x 6 Steel - Gloss Black

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising.

Rear Suspension	Dual A-Arm, IRS 10 in. (25.4 cm) Travel
This site uses cookies and related technologies, as described in our may include site operation, analytics, enhanced user experience, or	