

UTILITY VEHICLES

Taylor-Dunn utility vehicles deliver maximum durability and optimal performance while reducing your operating and maintenance costs.













			Burden Carriers		
	MX-600	C-432	Bigfoot S	Bigfoot	Bigfoot XL
Speed	9 mph (14 kmh)	9 mph (14 kmh)	11 mph (18 kmh)	12 mph (19 kmh)	18 mph (29 kmh)
Range	20 miles	20 miles	40-50 miles	40-60 miles	40-60 miles
Passenger Capacity	1	1	2	2-4	2-4
Payload Capacity	600 lbs	1,400 lbs	2,000 lbs	2,000 lbs	3,000 lbs
Tow Capacity	2,000 lbs	8,750 lbs	5,000 lbs	7,500 lbs	10,000 lbs
Dimensions w/o Cab (LxWxH)	86 x 32 x 41 in (218 x 81 x 104 cm)	79 x 30 x 40 in (201 x 76 x 102 cm)	118.5 x 44 x 51.5 in (300 x 112 x 131 cm)	130.5 x 44 x 51.5 in (332 x 112 x 131 cm)	130.5 x 57 x 52 in (332 x 145 x 132 cm)
Voltage	24V	36V	36V	48V, Li-ion available	48V, Li-ion available
Turning Radius	81 in	70 in	115 in	137 in	145 in



MX-600

The ultimate maintenance cart for indoor and outdoor applications.



C-432

Narrow aisle utility vehicle for the tightest of spaces.



Bigfoot S

Compact footprint with tighter turns for smaller facilities.



Bigfoot

Our flagship burden carrier with big payload and big towing.



Bigfoot XL

Maximum towing for larger operations.

Factory-Engineered Custom Solutions

If you need a tailored solution, our product and engineering team will work with you to design a custom vehicle. With possibilities ranging from special paint colors to major frame modifications, our custom vehicles are manufactured with the same craftsmanship, quality, and care as our standard models.

